



Ultra Performance Multi-Grade Engine Oil

CAPRON MAGNATEC is manufactured based on a blend of high quality, high viscosity index, synthetic base oil and high technology additives to provide ultimate performance and protection in today`s passenger cars and diesel engines.

Performance levels & Characteristics

● API SL/CF

SAE Grade ►	10W-40	15W-40	20W-50	ASTM
▼ Characteristics				
Kinematic viscosity @100°C, cSt	15	15.5	19	D-445
Kinematic viscosity @40°C, cSt				D-445
Viscosity Index (VI)	150	145	120	D-2270
Flash Point , °C	210	210	220	D-92
Pour Point , °C	-30	-30	-24	D-97
TBN, mg KOH/g	7.5	8	7	D-2869
Density @15°C, g/m ³	0.870	0.870	0.890	D-1298
CCS, cP	@-25 °C ≤7000	@-25 °C ≤7000	@-15 °C ≤9500	D-5293

Applications

- For today`s passenger cars designed since 2011, naturally aspirated and supercharged diesel engines when above performance level and properties are recommended.

Advantages

- Advanced full synthetic formula prevents deposit and sludge which leads to longer engine life.
- Engine cleanliness and low combustion residue and anti-wear protection.
- Neutralizing generated acidic components
- Outstanding lubrication and mechanical protection of engine suitable for many driving styles.
- Significant thermal stability and oxidation resistance providing maximum oil change interval.
- Excellent thermal control which reduces fuel consumption.
- Significant low temperature flow for best start up and cold weather use with resistant oil film even in high temperature
- Superior shear stability leads to viscosity retention at all operating temperatures.

Available in : 5 L - 4 L - 1 L

