



Ultra Performance Multi-Grade Engine Oil

CAPRON MAGNATEC is manufactured based on a blend of high quality, high viscosity index, synthetic base oil and high technology additives to provide ultimate performance and protection in today`s passenger cars and diesel engines.

Performance levels & Characteristics

● API SM/CF

SAE Grade ►	5W-40	10W-40	ASTM
▼ Characteristics			
Kinematic viscosity @100°C, cSt	14.5	15	D-445
Kinematic viscosity @40°C, cSt			D-445
Viscosity Index (VI)	160	150	D-2270
Flash Point , °C	210	215	D-92
Pour Point , °C	-36	-30	D-97
TBN, mg KOH/g	8.2	8.5	D-2869
Density @15°C, g/m ³	0.875	0.880	D-1298
CCS, cP	@-30°C ≤6600	@-25°C ≤7000	D-5293

Applications

- For today`s passenger cars designed since 2011, naturally aspirated and supercharged diesel engines when above performance level and properties are recommended.

Advantages

- Advanced full synthetic formula prevents deposit and sludge which leads to longer engine life.
- Engine cleanliness and low combustion residue and anti-wear protection.
- Outstanding lubrication and mechanical protection of engine suitable for many driving styles.
- Significant thermal stability and oxidation resistance providing maximum oil change interval.
- Significant low temperature flow for best start up and cold weather use with resistant oil film even in high temperature
- Excellent detergency and dispersancy

Available in : 5 L - 4 L - 1 L

